erial No.

ocket No.

AMENDMENTS TO THE CLAIMS:

Please cancel claim 27 without prejudice or disclaimer, and amend the claims as follows:

(Currently Amended) A method of forming a semiconductor device, comprising:
 implanting, on a substrate, a dopant to form a dopant extension region; and
 implanting at least one species, on a substrate to form a region surrounding at least a
 portion of said dopant extension region; and

annealing said substrate, said at least one species retarding a diffusion of said dopant during said annealing of said substrate.

- 2. (Original) The method of claim 1, wherein a dosage of said at least one species exceeds a preamorphization threshold of said substrate.
- 3. (Currently Amended) The method of claim 1, wherein a dosage of said at least one species is comprises at least about 3 times the preamorphization threshold of said substrate.
- 4. (Currently Amended) The method of claim 1, wherein a dosage of said at least one species is comprises at least about 5 times the preamorphization threshold of said substrate.
- 5. (Currently Amended) The method of claim 1, wherein a dosage of said at least one species is comprises at least about 7 times the preamorphization threshold of said substrate.
- 6. (Original) The method of claim 1, wherein said at least one species damages a junction formed by the dopant.

Docket No. YOR920030077US1

- 3
- 7. (Currently Amended) The method of claim 6, wherein said junction has comprises a thickness depth of no more than about 30 nm.
- 8. (Currently Amended) The method of claim 6, wherein said junction has comprises a slope which is at least about 5 nm per decade of change in concentration of said dopant.
- 9. (Original)The method of claim 1, wherein said substrate comprises at least one of silicon, SiGe, strained Si and strained SiGe.
- 10. (Original) The method of claim 1, wherein said at least one species comprises at least one of Xe, Ge, Si, Ar, Kr, Ne, He and N.
- 11. (Original) The method of claim 1, wherein said dopant comprises at least one of As, P, and Sb.
- 12. (Original) The method of claim 1, wherein said dopant is implanted at a time which is one of prior to said implanting said species, and after said implanting said species.
- 13. (Currently Amended) The method of claim 1, further comprising:

 forming a source <u>region</u> and <u>a</u> drain region in said substrate; and

forming a metal silicide contact over said source region and said drain region.

Docket No. YOR920030077US1

4

14. (Currently Amended) The method of claim 13, wherein said source <u>region</u> and <u>said</u> drain region are formed at a time which is prior to said implanting of said dopant.

- 15. (Currently Amended) The method of claim 13, wherein said source <u>region</u> and <u>said</u> drain region are formed at a time which is after said implanting of said dopant.
- 16. (Original) The method of claim 14, wherein said dopant is implanted at a time which is one of prior to said implanting said species, and after said implanting said species.
- 17. (Original) The method of claim 15, wherein said dopant is implanted at a time which is one of prior to said implanting said species, and after said implanting said species.
- 18. (Original) The method of claim 1, wherein said species is implanted at least about 10 to about 20 nm deeper than said dopant.
- 19. (Currently Amended) The method of claim 1, wherein said species has an implantation energy sufficient to create a <u>said</u> region surrounding at least a portion of an <u>said dopant</u> extension region in said substrate.
- 20. (Currently Amended) The method of claim 1, wherein said species has a first implantation energy sufficient to create a <u>said</u> region surrounding at least a portion of an <u>said dopant</u> extension region in said substrate, and a second implantation energy sufficient to create a region surrounding at least a portion of a source/drain region in said substrate.

Docket No. YOR920030077US1

- 21. (Currently Amended) The method of claim 1, wherein said species has an implantation energy sufficient to create a region surrounding at least a portion of an said extension region and at least a portion of a source/drain region in said substrate.
- 22. (Original) The method of claim 1, wherein said annealing said substrate is performed after said implanting said dopant and said implanting said species.
- 23. (Currently Amended) The method of claim 1, A method of forming a semiconductor device, comprising:

implanting, on a substrate, a dopant and at least one species; and

annealing said substrate, said at least one species retarding a diffusion of said dopant

during said annealing of said substrate,

wherein said implanting said dopant is performed after said implanting said at least one species, said method further comprising:

annealing said substrate after said implanting said species and before said implanting said dopant.

24. (Currently Amended) A method of forming a shallow and abrupt junction in <u>a</u> semiconductor substrate, comprising:

implanting a dopant on a substrate to form a dopant extension region;

implanting at least one species in a vicinity of said dopant in a dosage which far exceeds a preamorphization threshold of said substrate to form a region surrounding at least a portion of said dopant extension region; and

Docket No. YOR920030077US1

annealing said substrate, said at least one species retarding a diffusion of said dopant during said annealing of said substrate, such that a shallow and abrupt junction is formed.

6

- 25. (Currently Amended) A semiconductor device, comprising:
 - a semiconductor substrate;
 - a dopant formed in said substrate, to define a junction; and
- a species formed in a vicinity of said junction and in a concentration which far exceeds a preamorphization threshold of said substrate to form a region surrounding at least a portion of said junction.
- 26. (Currently Amended) The device of claim 25, further comprising:
 - a source region and a drain region formed adjacent said dopant and said species;
 - a channel formed between said source region and said drain region;
 - a gate formed over said channel; and
 - a contact formed over said source region and said drain regions region.
- 27. (Canceled)
- 28. (Currently Amended) The device of claim 26, wherein a region of said species surrounds at least a portion of said junction, and at least a portion of said source region and said drain regions region.

Docket No. YOR920030077US1

- 29. (Currently Amended) The device of claim 25, wherein said junction has comprises a thickness depth of no more than about 30 nm, and a slope which is at least about 5 nm per decade of change in concentration of dopant.
- 30. (Original) The device of claim 25, wherein said substrate comprises one of silicon, SiGe, and strained Si.
- 31. (Original) The device of claim 30, wherein said SiGe comprises one of relaxed SiGe and strained SiGe.
- 32. (Original) The device of claim 31, wherein said strained SiGe comprises SiGe under one of a compressive strain and a tensile strain.
- 33. (New) The method of claim 1, wherein said substrate comprises at least one of SiGe, strained Si, strained SiGe and relaxed SiGe.
- 34. (New) The method of claim 1, wherein said at least one species comprises at least one of Xe, Kr, Ne, He and N.
- 35. (New) The method of claim 25, wherein said at least one species comprises at least one of Xe, Kr, He and N.
- 36. (New) The method of claim 1, wherein said substrate comprises a graded SiGe layer having a crystal lattice which is more relaxed in a direction extending away from a top surface

Docket No. YOR920030077US1

of the substrate and a concentration of Ge that increases in a direction extending away from the top surface of the substrate.

8

- 37. (New) The method of claim 1, wherein said at least one species comprises a material that is different from said dopant.
- 38. (New) The method of claim 1, further comprising:
 forming a strained silicon channel adjacent said dopant extension region.
- 39. (New) The method according to claim 1, wherein said region surrounding at least a portion of said dopant extension region is formed under said dopant extension region and comprises a lip portion which extends along at least one side of said dopant extension region.
- 40. (New) The method according to claim 1, further comprising:

 forming a disposable spacer to mask a region where said dopant is implanted.